



## Special design for Green Pin Tycan®

The Green Pin Tycan® Sling Hook CL GR10 is a clevis sling hook with a safety latch that prevents the sling from sliding back.

These latches are also available separately as spares. The hook is made from grade 10, high tensile steel and is available in a range with a working load limit from 2.6 ton up to 10.3 ton and a lashing capacity of 10 and 13.6 ton.

For more information please contact us: [info@greenpin.com](mailto:info@greenpin.com)

## Product update

March 2022

### Green Pin Tycan® Sling Hook CL GR10

**Product code:** UCSCT  
**Material:** Alloy steel, grade 10, quenched and tempered  
**Safety Factor:** MBL equals 4 x WLL and MBL equals 2 x Lashing Capacity  
**Finish:** Painted blue  
**Temperature range:** -40°C up to +200°C (-40°F up to +392°F)

**Certification:**

2.1 2.2 3.1 MPI<sup>®</sup> MTC<sup>®</sup>

for chain size	working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
11x15	2.6	112	17	30	20	24	44	87	158	13	0.73
11x20	4	129	22	33	24	29	57	106	186	16	1.31
15x25	5	125,6	24	37	28,6	34,6	68	123,4	219,7	20	2.15
13x30	6.8	159	32	37	32	39	74	133	235	20	2.56
15x40	10.3	185	42	45	40	43	96	165	271	24	4.25

for chain size	working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
inch	t	a inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	i inch	lbs
7/16 X 19/32	2.6	4 12/32	21/32	1 3/16	25/32	15/16	1 3/4	3 7/16	6 7/32	1/2	1.61
7/16 X 25/32	4	5 3/32	7/8	1 5/16	15/16	1 5/32	2 1/4	4 3/16	7 5/16	5/8	2.88
19/32 X 1	5	4 15/16	15/16	1 7/16	1 1/8	1 11/32	2 11/16	4 7/8	8 5/8	13/16	4.74
1/2 X 1 3/16	6.8	6 1/4	1 1/4	1 15/32	1 1/4	1 17/32	2 29/32	5 1/4	9 1/4	25/32	5.64
19/32 X 1 9/16	10.3	7 9/32	1 21/32	1 3/4	1 9/16	1 11/16	3 3/4	6 1/2	10 21/32	15/16	9.37

