



## Special design for Green Pin Tycan®

The Green Pin Tycan® Connecting Link GR10 is used for Green Pin Tycan® chain slings.

The Connecting Link is made from grade 10, high tensile steel and is available in a range with a working load limit from 2.6 ton up to 10.3 ton and a lashing capacity of 10 and 13.6 ton.

For more information please contact us: [info@greenpin.com](mailto:info@greenpin.com)

## Product update

March 2022

### Green Pin Tycan® Connecting Link GR10

**Product code:** UMJT  
**Material:** Alloy steel, grade 10, quenched and tempered  
**Safety Factor:** MBL equals 4 x WLL and MBL equals 2 x Lashing Capacity  
**Finish:** Painted blue  
**Temperature range:** -40°C up to +200°C (-40°F up to +392°F)

**Certification:**

2.1 2.2 3.1 MPI<sup>®</sup> MTC<sup>®</sup>

Partnumber	for chain size	working load limit	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	diameter	weight each
	mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
GPUMJT15	11x15	2.6	9	57	14	20	55	16	19	13	0.21
GPUMJT20	11x20	4	12	66	18	23	64	18	23	16	0.36
GPUMJT30	13x30	6.8	16	83	21	32	85	24	28	20	0.75
GPUMJT40	15x40	10.3	19	103	25.5	40	107.5	28	34	24	1.46

Partnumber	for chain size	working load limit	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	diameter	weight each
	inch	t	a inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	lbs
GPUMJT15	7/16 x 19/32	2.6	11/32	2 1/4	9/16	25/32	2 5/32	5/8	3/4	1/2	0.46
GPUMJT20	7/16 x 25/32	4	15/32	2 19/32	23/32	29/32	2 17/32	23/32	29/32	5/8	0.79
GPUMJT30	1/2 x 1 3/16	6.8	5/8	3 9/32	13/16	1 1/4	3 11/32	15/16	1 1/8	25/32	1.65
GPUMJT40	19/32 x 1 9/16	10.3	3/4	4 1/16	31/32	1 9/16	4 7/32	1 1/8	1 11/32	15/16	3.22

