## The complete solution for your lifting job

## **Green Pin Tycan® lifting assembly components**

Green Pin Tycan® fibre chain offers all the performance and flexibility of steel chain but is eight times lighter than steel. A choice of five sizes of lifting chain with matching fittings allows you to manufacture a complete chain assembly with a Working Load Limit of up to 21.6 tons. The chain fittings, specially developed for use with Green Pin Tycan®, include a connecting link, a shortening hook and a sling hook. The clevis of the hooks and the bearing surface of the connecting link have been specially designed to perfectly fit Green Pin Tycan® chain links. This guarantees safe assembly of the chain and its fittings.

Below, you can find an overview of the complete lifting system and complementary products currently on offer, including the article codes for individual components.

		2.6t WLL* (1 leg sling)	4t WLL* (1 leg sling)	5t WLL* (1 leg sling)	6.8t WLL* (1 leg sling)	10.3t WLL* (1 leg sling)
Master links	O R	GPUMS18 (5.4t) GPUMTS22 (6.5t)	GPUMS22 (8.2t) GPUMTS28 (11t)	GPUMS22 (8.2t) GPUMTS28 (11t)	GPUMS25 (11.2t) GPUMTS36 (17.5t)	GPUMS30 (16t) GPUMTS38 (21.2t)
Connecting links	OMJT UMJ	GPUMJT15	GPUMJT20	GPUMJ13	GPUMJT30	GPUMJT40
Shorteners	UCRCT	GPUCRCT15	GPUCRCT20	GPUCRCT25	GPUCRCT30	GPUCRCT40
Chain	FCHLIFT	FCHLIFT1115	FCHLIFT1120	FCHLIFT1525	FCHLIFT1330	FCHLIFT1540
Sleeve	SLEEVE	SLEEVE111550	SLEEVE112050	SLEEVE152530 SLEEVE152550	SLEEVE133050	SLEEVE154050
Hooks	UCSCT	GPUCSCT15	GPUCSCT20	GPUCSCT25	GPUCSCT30	GPUCSCT40
* 2 leg sling < 45 degrees		3.69 ton	5.65 ton	7 ton	9.6 ton	14.4 ton
* 2 leg sling 45-60 degrees		2.6 ton	4 ton	5 ton	6.8 ton	10.3 ton
* 3/4 leg sling < 45 degrees		5.5 ton	8.5 ton	10.5 ton	14.2 ton	21.6 ton
* 3/4 leg sling 45-60 degrees		3.9 ton	6 ton	7.5 ton	10.2 ton	15.5 ton





## The complete solution for your lashing job

## **Green Pin Tycan® lashing assembly components**

Green Pin Tycan® fibre chain offers all the performance and flexibility of steel chain but is eight times lighter than steel. Green Pin Tycan® Lashing Chain with a lashing capacity (LC) of 10 ton or 13.6 ton and a loadbinder with hooks, specially developed for use with Green Pin Tycan®, provide the best possible load securing during transport.

Below, you can find an overview of the complete lashing system and complementary products currently on offer, including the article codes for individual components.

		10t LC	13.6t LC
Loadbinder	P-7180	LCRR25ZHENT	LCRR25ZHENT
Connecting links	GMU TEMU	GPUMJ13	GPUMJT30
Shorteners	UCRCT	GPUCRCT25	GPUCRCT30
Chain	FCHLASH	FCHLASH1525	FCHLASH1330
Sleeve	SLEEVE	SLEEVE152530 SLEEVE152550	SLEEVE133050
Hooks	UCSCT	GPUCSCT25	GPUCSCT30



