



C



E-6260



Wire Rope Clip

Generally to EN 13411-5 Type A

- **Material:** bridge: malleable steel
U-bolt: mild steel
- **Standard:** EN 13411-5 Type A
formerly DIN 1142
- **Finish:** electro-galvanized
- **Certification:** 2.1

diameter wire rope	diameter a	length bow b	width inside c	length thread d	length base e	thickness base f	height base g	weight per 100 pcs
mm	mm	mm	mm	mm	mm	mm	mm	kg
5	5	25	12	14	25	13	13	2
6.5	6	32	14	17	30	16	14	4
8	8	41	18	20	39	20	18	8.2
10	8	46	20	24	40	20	21	8.4
12	10	56	24	28	50	25	24	17
13	12	64	29	29	55	28	29	27.5
14	12	66	28	31	59	30	28	28.6
16	14	76	34	35	64	32	35	43
19	14	83	37	36	68	33	40	49
22	16	96	41	40	74	34	44	68
26	20	111	46	50	84	38	51	111
30	20	127	54	55	95	41	59	140
34	22	141	60	60	105	45	67	202
40	24	159	68	65	117	49	77	268

C



Wire Rope Clip

Generally to DIN 741



E-6220

- **Material:** bridge: casted
U-bolt: mild steel
- **Standard:** formerly DIN 741
- **Finish:** electro-galvanized
- **Certification:** 2.1



diameter wire rope	diameter	length bow	width inside	length thread	length base	thickness base	height base	weight per 100 pcs
mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
3	4	20	9	12	21	10	10	1.4
5	5	24	11	13	23	11	10	1.5
6	5	28	13	15	26	12	11	1.6
8	6	34	16	19	30	14	15	4.1
10	8	42	19	22	34	18	17	6
11	8	44	20	22	36	19	18	7
13	10	55	24	30	42	23	21	11.8
14	10	57	25	30	44	23	22	12.4
16	12	63	29	33	50	26	26	21
19	12	75	32	38	54	29	30	23.6
22	14	85	37	44	61	33	34	23.8
26	14	95	41	45	65	35	37	41
30	16	110	48	50	74	37	43	62
34	16	120	52	55	80	42	50	75
40	16	140	58	60	88	45	55	104
45	18	163	65	75	97	49	60	134
50	20	170	72	77	106	51	65	175