


C


Short link chain

Generally to DIN 766 and DIN 5685-3, commercial quality

- **Material:** mild steel, grade 3
- **Standard:** generally to DIN 766 and DIN 5685-3
- **Finish:** electro-galvanized or hot dipped galvanized
- **Certification:** 2.1
- **Note:** not to be used for lifting applications!



E-7661
G-7662




diameter	length inside	length outside	weight per meter
a mm	b mm	c mm	kg
3	16	11	0.17
4	16	14	0.32
5	18.5	17	0.5
6	18.5	20	0.75
7	22	23	1
8	24	26	1.35
9	27	30	1.8
10	28	34	2.25
11	31	36	2.7
13	36	44	3.8
16	45	54	5.8
18	50	60	7.3

C


Long link chain

Generally to DIN 763 and DIN 5685-1, commercial quality

- **Material:** mild steel, grade 3
- **Standard:** generally to DIN 763 and DIN 5685-1
- **Finish:** electro-galvanized or hot dipped galvanized
- **Certification:** 2.1
- **Note:** not to be used for lifting applications!



E-7631
G-7632



diameter	length inside	length outside	weight per meter
a mm	b mm	c mm	kg
3	26	13	0.14
4	32	16	0.27
5	36	20	0.43
6	42	24	0.63
7	48	28	0.86
8	54	32	1.10
10	66	40	1.75
13	82	50	2.95
16	100	60	4.45