


C


Short link chain

Generally to DIN 766 and DIN 5685-3, commercial quality

- **Material:** mild steel, grade 3
- **Standard:** generally to DIN 766 and DIN 5685-3
- **Finish:** electro-galvanized (E) or hot dipped galvanized (G)
- **Certification:** 2.1
- **Note:** not to be used for lifting applications!



E-7661
G-7662




diameter	length inside	width outside	weight per meter
a mm	b mm	c mm	kg
3	16	11	0.17
4	16	14	0.32
5	18.5	17	0.50
6	18.5	20	0.75
7	22	23	1
8	24	26	1.35
9	27	30	1.80
10	28	34	2.25
11	31	36	2.70
13	36	44	3.80
16	45	54	5.80
18	50	60	7.30

C


Long link chain

Generally to DIN 763 and DIN 5685-1, commercial quality

- **Material:** mild steel, grade 3
- **Standard:** generally to DIN 763 and DIN 5685-1
- **Finish:** electro-galvanized (E) or hot dipped galvanized (G)
- **Certification:** 2.1
- **Note:** not to be used for lifting applications!



E-7631
G-7632




diameter	length inside	width outside	weight per meter
a mm	b mm	c mm	kg
3	26	13	0.14
4	32	16	0.27
5	36	20	0.43
6	42	24	0.63
7	48	28	0.86
8	54	32	1.10
10	66	40	1.75
13	82	50	2.95
16	100	60	4.45

C


Short link chain

Generally to DIN 766 and DIN 5685-3

- **Material:** AISI 316
- **Standard:** generally to DIN 766 and DIN 5685-3
- **Certification:** 2.1



R-7880




diameter	length inside	width outside	weight per meter
a mm	b mm	c mm	kg
3	16	11	0.17
4	16	14	0.32
5	18.5	17	0.50
6	18.5	20	0.75
8	24	26	1.35
10	28	34	2.25

C


Long link chain

Generally to DIN 763 and DIN 5685-1

- **Material:** AISI 316
- **Standard:** generally to DIN 763 and DIN 5685-1
- **Certification:** 2.1



R-7890



diameter	length inside	width outside	weight per meter
a mm	b mm	c mm	kg
3	26	12	0.14
4	32	16	0.27
5	36	20	0.43
6	42	24	0.63
7	48	28	0.86
8	54	32	1.10
10	66	40	1.75