



TYPE APPROVAL CERTIFICATE

Certificate No:
TAS00003F7
Revision No:
1

This is to certify:

That the lifting set component for offshore containers and portable offshore units

with type designation(s)

P-6810 Master links - GPMLDNVXX

P-6820 Sub assemblies - GPMLADNVXX

Issued to

Van Beest B.V.

Slidrecht, Zuid-Holland, Netherlands

is found to comply with

DNV standard DNV-ST-E271 – 2.7-1 Offshore containers, January 2021 (Amended October 2021)

DNV standard DNV-ST-E273 – 2.7-3 Portable offshore units, April 2016 (Amended October 2021)

ISO 10855-2:2018 Offshore containers and associated liftings sets – Part 2: Design, manufacture and testing of lifting sets

IMO/MSC Circular 860

EN 1677-4 Components for slings – Safety – Part 4: Links, Grade 8

Application :

Grade 8 links for lifting sets for offshore containers and portable offshore units

Issued at **Aberdeen** on **2022-11-25**

This Certificate is valid until **2026-06-30** .

for **DNV**

DNV local unit: **Rotterdam**

Approval Engineer: **Elisabeth Legg**

.....
Satya Shyamala Kuppili

Team Lead - Containers

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Manufactured by

DNV Id No.: 10698797

Responsibility

Van Beest B.V. takes responsibility that both design and production at all places of manufacture are in compliance with the Rules, Standards and/or Regulations listed on page 1 of this type approval certificate.

Product description

This type approval certificate replace previous revisions of TAS00003F7.

This approval covers master links, intermediate links and master link assemblies for use in lifting sets for units certified in accordance with DNV-ST-E271 or DNV-ST-E273.

Detailed product information of certified products covered by this type approval are listed in Appendix 1 of this type approval certificate.

DNV has accepted some components with internal dimensions smaller than those specified in EN 1677-4 Table 2. These are marked with * in Appendix 1.

Application/Limitation

Design temperature: - 40°C

- Master links: GPMLDNV16 (16 mm) to GPMLDNV50 (50 mm)
- Sub-assemblies: GPMLADNV16 (16 mm / 14.5 mm) to GPMLADNV50 (50 mm / 45 mm)

Design temperature: - 20°C

- Master links: GPMLDNV65 (65 mm) to GPMLDNV75 (75 mm)
- Sub-assemblies: GPMLADNV65 (65 mm / 50 mm) to GPMLADNV75 (75 mm / 65 mm)

Selection of the correct dimensions of lifting sets and/or lifting set components shall be carried out in accordance with the requirements for lifting sets of offshore containers in DNV-ST-E271 section 8.

Tests to be carried out:

- Production testing: in accordance with DNV-ST-E271 and EN 1677-4, in agreement with the DNV surveyor.
- Material to be impact tested by Charpy impact method in accordance with DNV-ST-E271 section 8.4.

Van Beest B.V. shall issue product certificates in accordance with DNV-ST-E271 section 8.5, using the certificate form KF-10-690A Issue 01.05.2022. This certificate form shall only be used for links certified in accordance with this type approval.

For links manufactured in accordance with DNV-ST-E271

The required Working Load Limit (WLL) for a given container rating should be determined in accordance with DNV-ST-E271 Table 8-1 and Van Beest B.V. procedure. In no case should an offshore container lifting set WLL be less than 7.0 tonnes.

For links manufactured in accordance with DNV-ST-E273

Prior to selection of links, the minimum required working load limit (WLL) shall be determined in accordance with the strength requirements for lifting sets on portable offshore units as given in DNV-ST-E273 section 7.3.5 and must be approved by DNV. Resultant sling force (RSF) can be found in the design verification report (DVR) issued by DNV for the portable offshore unit.



Job Id: **262.1-016123-8**
Certificate No: **TAS00003F7**
Revision No: **1**

Type Approval documentation

Tests carried out

Prototype testing shall be carried out in accordance with DNV-ST-E271.

Marking of product

Components shall be marked in accordance with EN 1677-4 chapter 7.1, DNV-ST-E271 section 8 or DNV-ST-E273 section 7, as appropriate.

Periodical assessment

In order to maintain the validity of the type approval certificate, periodical assessments should be carried out by a DNV surveyor every 12 months.

END OF CERTIFICATE

Appendix 1

Product description and details:

The values of the working load limit (WLL) specified below are nominal for each component and the correct selection shall be made in accordance with DNV-ST-E271 section 8.

P-6810 Master links:

Type	Description	Diameter [mm]	Working Load Limit (WLL) [t]	Manufacturing Proof Force (MPF) [kN]	Minimum Breaking Force (BF) [kN]
GPMLDENV16 **	GP 8 MLDENV16-5/8	16	4.1	101	201
GPMLDENV22	GP 8 MLDENV22-7/8	22	7.0	172	343
GPMLDENV26	GP 8 MLDENV26-1	25.5	9.3	229	456
GPMLDENV28	GP 8 MLDENV28-1 1/8	28	14.5	356	711
GPMLDENV28S *	GP 8 MLDENV28S-1 1/8	28	19.5	479	956
GPMLDENV32	GP 8 MLDENV32-1 1/4	32	19.0	466	932
GPMLDENV36	GP 8 MLDENV36-1 3/8	36	26.0	638	1275
GPMLDENV40	GP 8 MLDENV40-1 9/16	40	30.5	749	1496
GPMLDENV45	GP 8 MLDENV45-1 3/4	45	40.0	981	1962
GPMLDENV50	GP 8 MLDENV50-2	50	51.0	1251	2502
GPMLDENV65	GP 8 MLDENV65-2 9/16	65	75.0	1840	3679
GPMLDENV75	GP 8 MLDENV75-3	75	100.0	2453	4905

*) Non-standard sizes, see comment under Product description.

**) This size shall only be used for portable offshore units.

P-6820 Sub assemblies:

Type	Description	Diameter [mm]	Working Load Limit (WLL) [t]	Manufacturing Proof Force (MPF) [kN]	Minimum Breaking Force (BF) [kN]
GPMLADNV16 **	GP 8 MLADNV16-14-5/8	16 / 14.5	4.1	101	201
GPMLADNV22	GP 8 MLADNV22-22-7/8	22 / 22	7.0	172	343
GPMLADNV26	GP 8 MLADNV26-22-1	25.5 / 22	9.3	229	456
GPMLADNV28	GP 8 MLADNV28-22-1 1/8	28 / 22	14.5	356	711
GPMLADNV32	GP 8 MLADNV32-28-1 1/4	32 / 28	19.0	466	932
GPMLADNV36	GP 8 MLADNV36-28-1 3/8	36 / 28	26.0	638	1275
GPMLADNV40	GP 8 MLADNV40-32-1 9/16	40 / 32	30.5	749	1496
GPMLADNV45	GP 8 MLADNV45-36-1 3/4	45 / 36	40.0	981	1962
GPMLADNV50	GP 8 MLADNV50-45-2	50 / 45	51.0	1251	2502
GPMLADNV65	GP 8 MLADNV65-50-2 9/16	65 / 50	75.0	1840	3679
GPMLADNV75	GP 8 MLADNV75-65-3	75 / 65	100.0	2453	4905

**) This size shall only be used for portable offshore units.